

• Model: AP-C4000 SR

Dio Trues accordances

FRONTVIEW



SIDE VIEW



• Remote controller (Option)



FEATURES

- ▶ High Resolution of 540TV Line
- 1/3" Super HAD color CCD with 410K Pixels
- Back Light Compensation
- Motion Detection / Day & Night
- OSD (On Screen Display)
- Privacy Image Masking with Free Position: 4Zones
- Min.illumination of 0.3 LUX @ F1.2 (Normal Color Mode)

0.002 LUX @ F1.2(Sens-up)

Option - Dual Power (DC12V & AC24V / AC 230V) RS-485 PORT / Remote Controller

ICR (IR cut filter removeable)



■ Standard □ Option

SPECIFICATIONS

DESCRIPTION

- Image Pick-Up Device
- TV System
- Pixels
- Scanning System
- Sync System
- Resolution
- Minimum Illumination
- S/N Ratio
- White Balance
- Gamma Characteristic
- Video output
- Electronic shutter Speed

AP-C4000 SR

Device 1/3" SONY SUPER HAD CCD

NTSC/PAL

NTSC=768(H)X 494(V)

PAL=755(H)X 582(V)

2:1 Interlaced

Line Lock (AC) / Internal (DC)

540TV Line

0.002Lux (Sens-Up X 128)

More than 50 dB

ATW/AWC/MANUAL (1800K~10,500'K)

0.45

1.0Vp-p 75 ohm Composite

NTSC: AUTO/MANUAL (X128~1/60SEC~-1/120,000sec)
SENS-UP & SENS-UP LIMIT IS SELECTABLE / FLICKERLE

PAL: AUTO/MANUAL (X128~1/50SEC~-1/120,000sec) SENS-UP & SENS-UP LIMIT IS SELECTABLE/FLICKERLE

DESCRIPTION

-) OSD) BLC
- AGC
- DNR
- DAY&NIGHT
- MOTION DETECTION
- MIRROR
- SHARPNESS
- PRIVACY
- Power Supply
- Power Consumption
- Lens
- Operational Temperature
- Storage Temperature
- Weight

AP-C4000 SR

- BUILT-IN
- LOW, MIDDLE, HIGH, OFF SELECTABLE
- LOW, MIDDLE, HIGH, OFF SELECTABLE
- LOW, MIDDLE, HIGH, OFF SELECTABLE
- AUTO/ON
- ON/OFF (4ZONE)
- ON/OFF
- ON/OFF (LEVEL ADJUSTABLE)
- ON/OFF (4 ZONE)
- DC12V/AC24V/AC230V (Option)
- 150mA
- C/CS mount lens
- -10Deg~+50 Deg C RH95% Max
- -20Deg~+60 Deg CRH95% Max
- Appx.0.5Kg